

## Granville Multi Hy-Vis 32

20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypalube Multi Hy-vis 32 hydraulic oil is a high viscosity index fluid formulated for use in a wide range of agricultural, commercial and industrial applications where recommended, they offers excellent pumpability and protect against oxidation and corrosion.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

DIN: 51524 Part 2 (HLP), 51524 Part 3 (HVLP) & 51524 Part 1 (HL)

ISO: 11158 (HL, HM, HV)

AFNOR: NF ISO 11158 (HL, HM, HV)

Vickers: 1.286.S

US Steel: 126 & 127



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6551	5020618065517
199 Litre	6553	5020618065531

### PRODUCT BENEFITS

- \*High viscosity index
- \*Excellent pumpability
- \*Protect against oxidation and corrosion

### STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and keep out of the reach of children

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Biodiesel</b>	: Nil



# Granville Multi Hy-Vis 32

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	28.8	35.2	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

